

Horizontal Hydraulic Folding Cast Rollers

3 Section

- 6.3m (21'), 7.2m (24') or 8.1m (27') working widths
- Robust fabricated steel frame
- Large wheels and tyres for fast smooth road transport
- Transport wheels are well clear of ground when rolling
- Simple adjustment of rings with cam adjusters
- Pivoting wing sections allow rolls to follow ground contours
- Transport lock for wing sections
- Ring size options




Transport position



Castellated Ring Profiles

Castellated rings are unique to Twose and fitted as standard.

The castellated ring profile has outstanding clod breaking and tilling characteristics to produce a surface seed bed with good capillary action and maximum crop establishment.



Rolling width	6.3m (21')			7.2m (24')			8.1m (27')				
Ring type	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings		
Diameter of rings	55cm (22")	55cm (22")	61cm (24")	55cm (22")	55cm (22")	61cm (24")	55cm (22")	55cm (22")	61cm (24")		
Product code	UHF/24/C1	UHF/21/CB4	UHF/21/CB5	UHF/21/LC2	UHF/24/C1	UHF/24/CB4	UHF/24/CB5	UHF/24/LC2	UHF/27/C1	UHF/27/CB4	UHF/27/LC2
Weight	3100kg	3750kg	4100kg	3440kg	3400kg	4150kg	4500kg	3805kg	3700kg	4590kg	4245kg
Transport width	2.93m (9'7")			2.93m (9'7")			2.93m (9'7")				
Tyre size	10.0/75 x 15.3 - 10 ply			10.0/75 x 15.3 - 10 ply			12.5/80 x 15.3 - 14 ply				
Bearing and axle diameter	65mm (2.5")			65mm (2.5")			65mm (2.5")				

Front Mounted Presses

- Choice of 10 models
- Self-steering mechanism
- Heavy duty three point linkage headstock
- Galvanised cleaning chains
- Ring diameter 700mm
- Ring profile options: 45° for use in all soil types
30° for heavier soil types
- Optional two rows of spring steel tines



Front mounted press



Press working width	1.5m (4' 11")		3.0m (9' 10")		4.0m (13' 01")		3.0m (9' 10") Hydraulic Folding		4.0m (13' 01") Hydraulic Folding	
Product code	FP1530	FP1545	FP3030	FP3045	FP4030	FP4045	FPF3030	FPF3045	FPF4030	FPF4045
Ring profile	30°	45°	30°	45°	30°	45°	30°	45°	30°	45°
Weight	863kg	936kg	1430kg	1660kg	1760kg	2000kg	1480kg	1670kg	1760kg	2000kg