

## Twose Drum Mowers

- 1.65m (5' 5"), 1.85m (6' 1") & 2.20m (7' 3") cutting widths
- 540 PTO over-run clutch
- Solid construction
- Double keys on all spiral gears
- Mechanical breakback
- Three point linkage mounted Cat I & Cat II
- Quick and simple replacement of blades
- Manual fold back for transport
- Low power requirement
- Centre pivot headstock
- Uniform spring assisted weight distribution on drums
- Excellent mowing in all conditions
- Three V-belt primary drive



Transport Position

Machine Type	Drum Mower 165	Drum Mower 185	Drum Mower 220
Cutting Width (m/ft)	1.65 / 5'5"	1.85 / 6'1"	2.20 / 7'3"
Tractor hp	40	50	55
Weight (kg)	392	425	490
Attachment (3-point linkage)	Cat. I & II	Cat. I & II	Cat. I & II
Transport Width (m)	1.34	1.46	1.49
Transport Length (m)	2.85	3.3	3.95
PTO Running Speed (rpm)	540	540	540
Drum Rotation (rpm)	1950	1725	1530
Number of Drums	2	2	2
Number of Blades	6	6	8

## Twose Rotary Rakes

- 4.3m (14' 1") and 4.7m (15' 5") working widths
- Solid construction
- Tandem walking axles with balloon tyres
- Pivoting headstock
- Narrow transport width
- Simple cam adjustment of tines
- Stepless height adjustment of tines
- 540 PTO slip clutch protected
- High work rate



Transport Position

Machine Type	RR 430	RR 470
Working Width (m/ft)	4.3 / 14'1"	4.7 / 15'5"
Tractor hp	40	50
Weight (kg)	480	540
Attachment (3-point linkage)	Pivoting	Pivoting
Transport Width (m)	1.64	2.23
PTO Running Speed (rpm)	540	540
Number of Rotors	1	1
Rotor Diameter (m)	3.3	3.6
Arms Per Rotor	12	13