

# Twose Silvercut Disc Mowers & Conditioners

- 2.5m, 2.9m and 3.25m cutting widths
- Finger conditioning option
- Three- point linkage- mounting
- Quick and easy blade replacement
- Disc protection
- Curved forged skids
- Paired, rotating disc's
- Safety breakback
- Heavy duty construction
- Hydraulic folding
- 1000 PTO slip clutch and over-run protection



Silvercut 300S



Silvercut 300SFC - finger conditioner

Machine Type	Silvercut 270SFC	Silvercut 300SFC
Cutting width m (ft)	2.5 / 8'10"	2.9 / 9'5"
Tractor hp	75hp	80hp
Weight (kg)	960kg	1060kg
3-point linkage	Cat. II	Cat. II
PTO Running Speed	1000rpm	1000rpm
Number of Discs	6	7
Number of Blades	12	14

Machine Type	Silvercut 270	Silvercut 300	Silvercut 340
Cutting width m (ft)	2.5 / 8'10"	2.90 / 9'5"	3.25 / 10'6"
Tractor hp	50hp	60hp	70hp
Weight (kg)	730kg	790kg	850kg
3-point linkage	Cat. II	Cat. II	Cat. II
PTO Running Speed	1000rpm	1000rpm	1000rpm
Number of Discs	6	7	8
Number of Blades	12	14	16