

Maxicut Rotary Topper Range

- Cutting width of 4.6m and 6.0m
- Cutting heights from 25mm to 375mm
- Hydraulic folding wings (112° movement)
- Self levelling deck linkage
- Compact transport widths
- Three rotors
- 150mm blade overlap
- 1000 rpm PTO
- Updraft blades
- Front and rear chain guards
- Slip clutch protection
- Light bar



Maxicut 460

Machine Type	Maxicut 460	Maxicut 6000
Cutting Width	4.6m (15ft 1in)	6.0m (20ft)
Minimum Tractor	80hp	100hp
Weight	2300kg	3470kg
Cutting Height	25-375mm	25-375mm
Overall Width	4.75m (15ft 6in)	6.3m (20ft 6in)
Overall Length	4.47m (14ft 7in)	5.15m (16ft 9in)
Transport Width	2.34m (7ft 7in)	2.56m (8ft 4in)
Transport Height	2.25m (7ft 4in)	2.77m (9ft)
PTO Running Speed	1000rpm	1000rpm
Slip Clutch Protection	Yes	Yes
Number of Rotors	3	3
Number of Blades	9	9
Blade Tip Speed	4470 (m/mm)	4266 (m/mm)
Blade Overlap	150mm	150mm
Degree of Wing Travel	90° up, 22° down	90° up, 22° down
Number of Wheels	6	8
Replaceable Skids	Standard	Standard